

IN THE CLAIMS

Please cancel claims 6 and 10 without prejudice or disclaimer of subject matter.

Please amend claims 1, 4, 5 and 7 as follows.

1. (Currently Amended) A color display element comprising a unit pixel which is comprised of a plurality of sub-pixels comprising a first sub-pixel and a second sub-pixel, the second sub-pixel having a green color filter, and a medium which has an optical property modulated in accordance with a voltage applied to each of the sub-pixels and is located in each of the sub-pixels,

wherein the color display element has a means of applying a voltage to the first sub= ~~pixel a voltage which modulates and second sub-pixels, and~~

wherein an optical property of the medium located in the first sub-pixel is modulated in accordance with a voltage applied to the first sub-pixel in a range within which a brightness of light passing through the medium is variable and in a range within which a chromatic color assumed by light passing through the medium changes within red and blue, and ~~a means of applying to the second sub-pixel a voltage which modulates~~

wherein an optical property of the medium located in the second sub-pixel is modulated in accordance with a voltage applied to the second sub-pixel in a range within which a brightness of light passing through the medium is variable.

2 - 3. (Cancelled)

4. (Currently Amended) The color display element according to claim 1,
wherein a voltage making the light passing through the medium assume magenta
~~intermediate between red and blue~~ is applied to the first sub-pixel, and a voltage making the light
passing through the medium ~~has assume~~ a maximum brightness ~~in the range within which a~~
~~brightness of the light is variable of green~~ is applied to the second sub-pixel, whereby the unit
pixel displays white color.

5. (Currently Amended) The color display element according to claim 1, wherein the
first sub-pixel has a magenta color filter ~~of a color complementary to a color of the color filter of~~
~~the second sub-pixel~~.

6. (Cancelled)

7. (Currently Amended) The color display element according to claim 5, wherein a
voltage in the range within which the chromatic color changes is applied to the first sub-pixel, to
display a color as a result of overlapping the chromatic color and a color of the ~~complementary~~
magenta color filter with each other.

8. (Previously Presented) The color display element according to claim 5, wherein a voltage making the lights passing through the mediums have a maximum brightness in the range within which a brightness of the light is variable is applied to the first and second sub-pixels, whereby the unit pixel displays white color.

9. (Previously Presented) The color display element according to claim 5, wherein modulations of a same gray level in the range within which a brightness of the light is variable are applied to the first and second sub-pixels respectively, whereby an achromatic color of half tone is displayed in the unit pixel.

10. (Cancelled)

11. (Withdrawn) A color display element comprising at least one polarizing plate, a pair of substrates opposite to each other in which an electrode is formed, and a liquid crystal layer located between the substrates,

wherein the retardation of the liquid crystal layer is variable according to a voltage applied to the electrode, and a unit pixel of the color display element is comprised of a plurality of sub-pixels comprising a first sub-pixel wherein the retardation of the liquid crystal layer is modulated according to the voltage applied to the electrode in a range within which a brightness of light passing through the liquid crystal layer is variable and in a range within which a chromatic color assumed by light passing through the liquid crystal layer changes and a second

sub-pixel having a color filter wherein the retardation of the liquid crystal layer is modulated according to the voltage applied to the electrode in a range within which a brightness of light passing through the liquid crystal layer is variable.

12. (Cancelled)

13. (Withdrawn) The color display element according to claim 11, wherein an orientation of a liquid crystal of the liquid crystal layer varies over a range between a bend orientation and an almost perpendicular orientation in accordance with an application of the voltage.

14. (Withdrawn) The color display element according to claim 11, wherein a thickness of a cell of the second sub-pixel is smaller than that of the first sub-pixel.

15. (Withdrawn) The color display element according to claim 11, wherein the unit pixel is comprised of a third sub-pixel having a color filter, the first and second sub-pixels have a region reflecting light respectively, and the third sub-pixel has a region which transmits a light from the rear through the color filter.

16. (Withdrawn) The color display element according to claim 15, wherein the third sub-pixel is a sub-pixel wherein the retardation of the liquid crystal layer is modulated according

to the voltage applied to the electrode in a range within which a brightness of light passing through the liquid crystal layer is variable.

17. (Withdrawn) The color display element according to claim 16, wherein a thickness of a liquid crystal layer in the light-transmitting region of the third sub-pixel is smaller than twice the thickness of the liquid crystal layers in the light-reflecting regions of the first and second sub-pixels.

18. (Withdrawn) The color liquid crystal display element according to claim 17, wherein the thickness of the liquid crystal layer of the light-reflecting region is equal to the thickness of the liquid crystal layer of the light-transmitting region, and makes it possible to modulate the retardation in a range from 0 nm to 300 nm.

19. (Withdrawn) The color display element according to claim 15, wherein the third sub-pixel is composed of three sub-pixels having red, green and blue color filters respectively.

20. (Withdrawn) The color display element according to claim 19, wherein each of the three sub-pixels is a sub-pixel in which the retardation of the liquid crystal layer is modulated according to the voltage applied to the electrode in a range within which a brightness of light passing through the liquid crystal layer is variable.

21. (Previously Presented) A method for driving a color display element which contains a medium an optical property of which changes in accordance with an applied voltage, the element being comprised of a unit pixel comprised of a plurality of sub-pixels comprising a first sub-pixel and a second sub-pixel, the second sub-pixel having a green color filter, which comprises the steps of:

applying to the first sub-pixel a voltage modulating an optical property of the medium in a range within which a brightness of light passing through the medium is variable and in a range within which a chromatic color assumed by light passing through the medium changes within red and blue, and

applying to the second sub-pixel a voltage modulating an optical property of the medium in a range within a brightness of light passing through the medium is variable.

22 - 29. (Cancelled)